



Chemical protection

# ULTRANITRIL 492

Frequent contact | intermittent wear



CHEMICAL PROTECTION  
**TYPE A**

EN388



3101X

EN ISO 374-1



TYPE A  
AJKOPT

CAT.3



0334

EN ISO 374-5



VIRUS

DEXTERITY

EN 420:  
5/5



G2  
ISO 18889

Good mechanical resistance and long-lasting chemical protection

## SPECIFIC ADVANTAGES



### Comfort

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining



### Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)



### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



### Additional benefits

- Available in vending machine packaging

## INDUSTRIES

- Automotive/mechanical industry
- Local Authorities (Cleaning)
- Local Authorities (Parks and Public Spaces)
- Construction Industry (Masons / Plasterers)
- Construction Industry (Carpenters/Joiners)
- Agriculture sector

## APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Plant Treatment Products
- Handling oils, solvents, detergents
- Preparing coatings, varnishes
- Handling PVC-based glues



Chemical protection

# ULTRANITRIL 492

Frequent contact | intermittent wear

## LEGENDS

<b>EN388</b>	<b>MECHANICAL HAZARDS</b>
	<b>PERFORMANCE LEVELS (X = NOT TESTED)</b>
<b>3 1 0 1 X</b>	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance
<b>EN ISO 374-1</b>	<b>CHEMICAL RISKS</b>
	A: Methanol
<b>TYPE A</b>	J: n-Heptane
	K: Sodium hydroxide 40%
	O: Ammonia 25%
	P: Hydrogen peroxide 30%
	T: Formaldehyde 37%
	<b>PROTECTION FROM PESTICIDES</b>
<b>G2</b>	G2: Diluted & concentrated pesticides / Mechanical risk
<b>ISO 18889</b>	
<b>EN ISO 374-5</b>	<b>MICRO-ORGANISMS</b>
	Protection against bacteria, fungi and virus
<b>VIRUS</b>	

## PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colour.s	Green
Length (cm)	32
Thickness (mm)	0.38
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	6.4E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	5.8E+9 Ω

## LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 100 pairs/carton
-----------	------------------------------------------------

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1631
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France