ULTRANITRIL 381

Frequent contact | ultra-comfort wear

Maximum comfort and chemical protection

CHEMICAL PROTECTION **TYPE A**

EN388



3111A



EN407



EN ISO 374-1



TYPE A **JKLOPT**

CAT.3

EN ISO 374-5



0334

DEXTERITY

ISO 18889

EN 420: 5/5

SPECIFIC ADVANTAGES

Thermal protection

Added comfort and thermal insulation, due to the cotton-knit lining



Comfort

Extremely supple, due to the unique Mapa multi-layer process



Productivity

Good grip on slippery objects, due to the embossed texture



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Additionnal benefits

Available in vending machine packaging

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

APPLICATIONS

- Laboratory tests
- Machine maintenance
- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Chemical product blending
- Handling drums of chemical products



ULTRANITRIL 381

Frequent contact | ultra-comfort wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

3 1 1 1 A A P P Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance
Tear resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT



Blade cut resistance

Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant

Contact heat resistance
Limited flame spread

EN ISO 374-1



TYPE A

CHEMICAL RISKS
J: n-Heptane

- K: Sodium hydroxide 40%
- L: Sulphuric acid 96%
- O: Ammonia 25%
- P: Hydrogen peroxide 30%
- T: Formaldehyde 37%



PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5

MICRO-ORGANISMS



Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Feston Cuff
Colour.s	Green
Length (cm)	36
Thickness (mm)	0.95
Size	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	7.6E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.9E+10 Ω

LOGISTIC DETAILS

		12 pairs/bag 72 pairs/carton
--	--	---------------------------------

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1663 updated 02-08/10/2021
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

